

IRON-50 Ex 12 or 24 VDC 0.18 kW · 50 l/min

Liquids:  **Diesel**  **Petrol**

IRON-50 Ex 12 VDC · 50 l/min

10063

IRON-50 Ex 24 VDC · 50 l/min

10153

- Self-suction - self-priming, explosionproof, eccentric with self-adjusting blades
- With recirculation bypass
- Suction: 2.7 m
- Priming pipe suction: 5 m
- Free flow: 50 l/min
- Consumption: 20-27 A (12 VDC) · 10-14 A (24 VDC)
- Motor: 0.18 kW 12 or 24 VDC EExd
- With thermal protector
- 3,000 rpm
- S2 30' operation
- IP-55 protection
- Operation temperature: -10 °C · +40 °C
- ATEX Class: II2G
- Protection mode (own supply): Ex h IIB T4 Gb
- Thread connection: F1" (BSP) and flange
- ON/OFF switch
- 3 m cable
- Anti-rust treatment



Size and weight (approx.):

- Dim.: 265x165x155 mm (length x width x height)
- Weight: 11.4 kg

SA-50 Ex 12 or 24 VDC · Pump with litre meter

Liquids: ● Diesel ● Petrol

IRON-50 Ex 12 or 24 VDC pump + MG-80AV mechanical aluminium meter with Viton joints

SA-50 Ex 12 VDC + MG-80AV

SA-50 Ex 12 VDC + MG-80AV + Base no. 4

31960-
CF00000

33340-
CF00000



©2008 **GESPASA · TOT COMERCIAL S.A.** · NIF A25031154 · Partida Horta d'Amunt s/n · Apartat de Correus núm. 149 · 25600 · BALAGUER (Lleida) SPAIN

Tel.: ++34 (9)73 45 10 72 · Fax: ++34 (9)73 44 84 00 · [PRIVACY POLICY](#) · www.cenics.net