




A100 Series Quarter Turn Electric Actuators

A100 series electric actuators are manufactured for on/off or proportional control of quarter turn butterfly, ball and plug valves and dampers.

The electric actuators are manufactured according to industrial standards with high quality for iron and steel, chemical, marine, mining, paper, cement plants, as well as general industrial applications and water treatment plants, HVAC sector.

The electric actuators have the complete compliance with ISO5211 flange standard which allow the direct mounting to the valves with the same Standard.



Technical Specifications

Torque Output	20 Models available with torques ranging from 30-20000 Nm to meet specific requirements.
Housing	Hard anodized aluminum casting and external epoxy powder coating against severe industrial applications.
Protection Class	IP67 as standard and IP68 upon request.
Sealing	Enhanced by Double O-ring in all interfaces.
Self Locking	Provided by double worm gearing to keep position of valve unchanged against reverse torque exerted by valve.
Emergency Manual Operation	8 mm Hex Shaft for PRO 30 & PRO 50 Nm, Clutch-free manual override handwheel for PRO 80 and above sizes
Motor	Specially designed induction motor to generate high starting torque and high efficiency equipped with thermal protector to prevent damage from over heating.
Limit Switches	Directly engaged with driving shaft to set accurate position of valve.
Torque Limit Switches	Protects actuator from damage caused by overload from the driven valve over the whole travel. Standard available on PRO 100 and over sizes.
Anti Condensation Heater	5W Anti condensation heaters prevent condensation. For severe weather conditions additional heaters provided optionally.
External Mechanical Stopper	Prevents over run of travel angle in case limit switches fails.
Position Indicator	Continuous mechanical position indicator and window with dial.
Terminal Strip	Spring loaded push type terminal strip for secure wiring connection under severe vibration.
Ambient Temperature Range	-30 °C to +70 °C
Humidity Range	0-95% RH
Motor Starts, per Hour Max	600
Max Altitude	3000 mt

A100 Series Quarter Turn Electric Actuators Technical Information,

Model Number	Item Code	Power Supply	Torque (Nm)	Torque Switch	Cycle Time (Sec.)	Motor Power (W)	Duty Cycle		Current Draw (A)		
							On/Off	Modulating	Start	Run	LRA
PRO 030	A100FEP2003	24VDC	30	N/A	11	10W	25%	50%	1,88	0,75	1,45
	A100FEP3003	220VAC (50/60Hz)					25%	50%	0,13	0,05	0,10
PRO 050	A100FEP2005	24VDC	50	N/A	10	6W	25%	50%	2,25	0,9	1,80
	A100FEP3005	220VAC (50/60Hz)			15/13	10W	25%	50%	0,53	0,21	0,50
PRO 080	A100FEP2008	24VDC	80	N/A	15	10W	25%	50%	2,25	0,9	1,80
	A100FEP3008	220VAC (50/60Hz)			22/18		25%	50%	0,50	0,21	0,50
PRO 100	A100FEP2010	24VDC	100	√	14	40W	25%	50%	8,00	3,2	6,00
	A100FEP3010	220VAC (50/60Hz)			19/16		25%	50%	1,00	0,42	0,80
	A100FEP4010	380VAC			19/16		25%	50%	0,80	0,32	0,60
PRO 200	A100FEP2020	24VDC	200	√	28	40W	25%	50%	8,00	3,2	6,00
	A100FEP3020	220VAC (50/60Hz)			39/33		25%	50%	1,00	0,42	0,80
	A100FEP4020	380VAC			39/33		25%	50%	0,80	0,32	0,60
PRO 300	A100FEP2030	24VDC	300	√	28	90W	25%	33%	8,50	3,5	6,50
	A100FEP3030	220VAC (50/60Hz)			39/33		25%	33%	1,15	0,46	0,85
	A100FEP4030	380VAC			39/33		25%	33%	0,80	0,35	0,65
PRO 400	A100FEP2040	24VDC	400	√	21	90W	25%	50%	14,00	5,6	10,50
	A100FEP3040	220VAC (50/60Hz)			29/24		25%	50%	2,20	0,9	1,80
	A100FEP4040	380VAC			29/24		25%	50%	1,50	0,62	1,20
PRO 600	A100FEP2060	24VDC	600	√	28	90W	25%	50%	14,00	5,6	10,50
	A100FEP3060	220VAC (50/60Hz)			39/33		25%	50%	2,20	0,9	1,80
	A100FEP4060	380VAC			39/33		25%	50%	1,50	0,62	1,20
PRO 800	A100FEP2080	24VDC	800	√	34	120W	25%	50%	14,00	5,6	10,50
	A100FEP3080	220VAC (50/60Hz)			47/39		25%	50%	2,20	0,9	1,80
	A100FEP4080	380VAC			47/39		25%	50%	1,50	0,62	1,20
PRO 1000	A100FEP2100	24VDC	1000	√	34	120W	25%	50%	20,00	8,4	16,00
	A100FEP3100	220VAC (50/60Hz)			47/39		25%	50%	2,50	1,1	2,00
	A100FEP4100	380VAC			47/39		25%	50%	2,00	0,8	1,50
PRO 1300	A100FEP3130	220VAC (50/60Hz)	1300	√	47/39	120W	25%	33%	3,20	1,3	2,50
	A100FEP4130	380VAC			47/39		25%	33%	2,30	0,92	1,75
PRO 1700	A100FEP3170	220VAC (50/60Hz)	1700	√	34/28	200W	25%	33%	5,50	2,2	4,00
	A100FEP4170	380VAC			34/28		25%	33%	2,50	1,1	2,00
PRO 2000	A100FEP3200	220VAC (50/60Hz)	2000	√	34/28	200W	25%	33%	6,20	2,5	4,50
	A100FEP4200	380VAC			34/28		25%	33%	3,20	1,3	2,50
PRO 2300	A100FEP3230	220VAC (50/60Hz)	2300	√	47/39	200W	25%	33%	5,50	2,2	4,50
	A100FEP4230	380VAC			47/39		25%	33%	2,50	1,1	2,00
PRO 3500	A100FEP3350	220VAC (50/60Hz)	3500	√	76/63	200W	25%	33%	5,50	2,2	4,50
	A100FEP4350	380VAC			76/63		25%	33%	2,50	1,1	2,00
PRO 5000	A100FEP3500	220VAC (50/60Hz)	5000	√	105/88	400W	25%	33%	5,50	2,2	4,50
	A100FEP4500	380VAC			105/88		25%	33%	2,50	1,1	2,00
PRO 8000	A100FEP3800	220VAC (50/60Hz)	8000	√	143/119	400W	25%	33%	5,50	2,2	4,50
	A100FEP4800	380VAC			143/119		25%	33%	2,50	1,1	2,00
PRO 13000	A100FEP41300	380VAC	13000	√	109/91	400W	25%	33%	5,00	2,00	3,60
PRO 16000	A100FEP41600	380VAC	16000	√	129/108		25%	33%	5,00	2,00	3,60
PRO 20000	A100FEP42000	380VAC	20000	√	155/129		25%	33%	5,00	2,00	3,60


A100 Quarter Turn Electric Actuators

PRO 030 Model Electric Actuators

Model	PRO 030
Series	A100 FEP
Supply	24V AC/DC , 110V AC , 220V AC
Torque	30 Nm
F1/F2/F3	F03/F04/F05
Spindle Shaft	11x11
Weight (Kg)	1.0 Kg

Optional Accessories

IP68 Protection Class
Potentiometer (1 K Ohm)
RPC - 4-20 mA Remote Proportional Control Unit
4-20 mA Position Transmitter




PRO 050 Model Electric Actuators

Model	PRO 050
Series	A100 FEP
Supply	24V AC/DC , 110V AC , 220V AC
Torque	50 Nm
F1/F2/F3	F05/F07
Spindle Shaft	14x14
Weight (Kg)	3.0 Kg

Optional Accessories

IP68 Protection Class
Potentiometer (1 K Ohm)
RPC - 4-20 mA Remote Proportional Control Unit
Local Control Unit
4-20 mA Position Transmitter
Fail-Safe Battery Back-Up




PRO 080 Model Electric Actuators



Model	PRO 080
Series	A100 FEP
Supply	24V AC/DC , 110V AC , 220V AC
Torque	80 Nm
F1/F2/F3	F05/F07
Spindle Shaft	14x14
Weight (Kg)	3.6 Kg

Optional Accessories



IP68 Protection Class
Potentiometer (1 K Ohm)
RPC - 4-20 mA Remote Proportional Control Unit
Local Control Unit
4-20 mA Position Transmitter
Fail-Safe Battery Back-Up




PRO 100 - 2300 Model Electric Actuators



PRO 3500 - 8000 Model Electric Actuators



PRO 13000 - 20000 Model Electric Actuators



Dimensions(mm)

Model	Item Code	Torque (Nm)	A	B	C	D	E	F	G	H	ISO5211 ØK	J	ISO5211 Top Flange	Conduit Entry	Unit Weight (Kg)
PRO 100	A100FEPX010	100	268	77	123	216	121	240	14X14 17X17	35	70	4-M8	F07 + F10	2 X PG16	11,00
PRO 200	A100FEPX020	200	268	77	123	216	121	240	14X14 17X17	35	70	4-M8	F07 + F10	2 X PG16	11,00
PRO 300	A100FEPX030	300	268	77	123	216	121	240	14X14 17X17	35	70	4-M8	F07 + F10	2 X PG16	22,00
PRO 400	A100FEPX040	400	327	103	187	266	150	297	22x22	55	102	4-M10	F10 + F12	2 X PG16	22,00
PRO 600	A100FEPX060	600	327	103	187	266	150	297	22x22 27x27	55	102 125	4-M10 4-M12	F10 + F12	2 X PG16	22,00
PRO 800	A100FEPX080	800	327	103	187	266	150	297	27x27	55	125	4-M12	F14	2 X PG16	22,00
PRO 1000	A100FEPX100	1000	327	103	187	266	150	297	27x27	55	125	4-M12	F14	2 X PG16	22,00
PRO 1300	A100FEPX130	1300	327	103	187	266	150	297	27x27	55	125	4-M12	F14		22,00
PRO 1700	A100FEPX170	1700	380	127	242	293	161	333	27x27	65	125 140	4-M16 4-M20	F14	2 X PG16	36,00
PRO 2000	A100FEPX200	2000	380	127	242	293	161	333	27x27	65	125 140	4-M16 4-M20	F14	2 X PG16	36,00
PRO 2300	A100FEPX230	2300	380	127	242	293	161	333	36x36	65	125 140	4-M16 4-M20	F16	2 X PG16	36,00
PRO 3500	A100FEPX350	3500	532	118	242	293	308	186	40x40	85	140 165	4-M16 4-M20	F16	2 X PG16	76,00
PRO 5000	A100FEPX500	5000	532	118	242	293	308	186	46x46	85	165	4-M20	F16	2 X PG16	76,00
PRO 8000	A100FEPX800	8000	545	160	242	293	343	160	55x55	130	254	8-M16	F25	2 X PG16	107,00
PRO 13000	A100FEPX1300	13000	672	520	-	293	281	331	55x55 75x75	120	254	8-M16	F25 / F30	2 X PG16	218,00
PRO 16000	A100FEPX1600	16000	672	520	-	293	281	331	55x55 75x75	120	298	8-M20	F25 / F30	2 X PG16	218,00
PRO 20000	A100FEPX2000	20000	672	520	-	293	281	331	55x55 75x75	120	298	8-M20	F25 / F30	2 X PG16	218,00

*X refers to power supply. X-2 for 24VDC, X-3 for 220VAC, X-4 for 380VAC actuators