

AG-900 12 VDC EExd · 0.37 kW · 80 l/min

Liquids:  **Diesel**  **Petrol**

AG-900 12 VDC 70-80 l/min

10070



- Self-suction - self-priming, explosionproof, eccentric with self-adjusting blades
- With recirculation bypass
- Suction: 2.7 m
- Priming pipe suction: 5 m
- Free flow: 70-80 l/min
- Consumption: 42-50 A
- Motor: 0.37 kW 12 VDC EExd
- 1,650 rpm
- S2 20' operation
- IP-55 protection
- Operation temperature: -10 °C · +40 °C
- ATEX Class: II2G
- Protection mode (own supply): Ex h IIB T4 Gb
- With thermal protector
- Connection: through F1" (BSP) threads and flanges
- ON/OFF switch
- 1.5 m cable
- Anti-rust treatment

Size and weight (approx.):

- Dim.: 400x165x155 mm (length x width x height)
- Weight: 19 kg

Optional:



- F1" aluminium flange kit 

800003022

SAG-900A Ex 12 VDC 80 l/min · Pump with litre meter

AG-900 12 VDC + MG-80AV mechanical aluminium meter with Viton joints

SAG-900A Ex 12 VDC + Base no. 4

33360-
CF00000

** Hose and nozzle not included*

Optionals:

- M1" long union flange kit in PA + fibreglass 
- Stainless filter-sieve of 350 µm (micron) Ø33 mm
- Universal support 

800003027
460000003
800404259



©2008 **GESPASA · TOT COMERCIAL S.A.** · NIF A25031154 · Partida Horta d'Amunt s/n · Apartat de Correus núm. 149 · 25600 · BALAGUER (Lleida) SPAIN
Tel.: ++34 (9)73 45 10 72 · Fax: ++34 (9)73 44 84 00 · [PRIVACY POLICY](#) · www.cenics.net