


Solenoid valves, to NAMUR


FESTO



Solenoid valves, to NAMUR

Product range overview

FESTO

Function	Version	Type	Nominal size [mm]	Standard nominal flow rate [l/min]	Pneumatic connection	Operating pressure [bar]	Ambient temperature [°C]
5/2-way valves ¹⁾		NVF3-...-EX	7	900	G1/4	2 ... 10	-5 ... +40
							ATEX: -5 °C ≤ Ta ≤ +40 °C
							ATEX: -5 °C ≤ Ta ≤ +40 °C

1) Can be changed to 3/2-way function by exchanging the seal plate

Solenoid valves, to NAMUR

Product range overview




Type	Solenoid coil	Operating voltage range		Ignition protection type			→ Page/Internet
		[V DC]	[V AC]	nA = Non-sparking	m = Encapsulation	ia = Intrinsically safe	
NVF3-...-EX	MSFG-...-OD ¹⁾ , MSFW-...-OD ¹⁾	12, 24, 42, 48	24, 42, 48, 110, 230, 240	–	–	–	6
	MSFG-...-EX ¹⁾ , MSFW-...-EX ¹⁾	24	24, 110, 230	■	–	–	
	MSFG-...-M-EX ¹⁾ , MSFW-...-M-EX ¹⁾	24	24, 110, 230	–	■	–	

1) Solenoid coil must be ordered separately

Solenoid valves NVF3, to NAMUR

Peripherals overview

FESTO



Solenoid valves NVF3, to NAMUR

Peripherals overview

FESTO

Solenoid valves and accessories			
	Brief description	➔ Page/Internet	
Solenoid valves			
[1]	NVF3-MOH-5/2K-1/4-EX	Solenoid valve for F solenoid coil	6
[2]	NVF3-MOH-5/2K-1/4-IA-EX	Solenoid valve mounted with intrinsically safe solenoid coil, ignition protection type ia = intrinsically safe	
Accessories			
[3]	Coding pin	Included in the scope of delivery	–
[4]	Seal plate	For changing the valve function, included in the scope of delivery	–
[5]	Solenoid coil MSFG-...-M-EX and MSFW-...-M-EX	Ignition protection type m = encapsulation	10
[6]	Solenoid coil MSFG-...-EX and MSFW-...-EX	Ignition protection type nA = non-sparking	
[7]	Illuminating seal MF-LD	For indicating the switching status	
[8]	Plug socket MSSD-F-M16	Insert can be repositioned by 180°. Ignition protection type nA = non-sparking for solenoid coil in item [6]	
[9]	Plug socket with cable KMF	Insert can be repositioned by 180°	
[10]	Plug socket MSSD-V-M16	Insert can be repositioned by 180°. Ignition protection type ia = intrinsically safe for solenoid coil in item [2]	
[11]	Inscription labels KMC/F/V-BZ	For identifying the plug sockets	


Solenoid valves NVF3, to NAMUR

FESTO

Technical data


Function¹⁾


5/2-way valve





3/2-way valve

with exhaust air return



-  - Voltage
12, 24, 42, 48 V DC
24, 42, 48, 110, 230, 240 V
AC

-  - Pressure
2 ... 10 bar

-  - Temperature range
-5 ... +40 °C
ATEX
-5 °C ≤ Ta ≤ +40 °C



1) Can be changed by exchanging the seal plate

General technical data			Solenoid valve with F coil of choice	Solenoid valve with mounted solenoid coil
Valve function			5/2-way or 3/2-way, single solenoid	
Conforms to			VDI/VDE 3845 (NAMUR)	
Width [mm]			53	
Design			Disk seat	
Sealing principle			Soft	
Actuation type			Electric	
Reset method			Mechanical spring	
Type of control			Piloted	
Direction of flow			Non-reversible	
Exhaust function			Flow control	
Manual override			Detenting, non-detenting	
Type of mounting			On manifold rail	
Mounting position			Any	
Lap			Underlap	
Vent connection			Internal	
Nominal size [mm]			7	
Standard nominal flow rate 1 → 2, 2 → 3 [l/min]			900	
Exhaust air return 2 → 4 [l/min]			150	
b value			0.33	
C value [l/sbar]			4.2	
Pneumatic connection 1, 3, 5			G1/4	
2, 4			Port pattern as per NAMUR	
Pilot exhaust port 84			M5	
Product weight [g]			280	350

Solenoid valves NVF3, to NAMUR

Technical data

Operating and environmental conditions		
	Solenoid valve with F coil of choice	Solenoid valve with mounted solenoid coil
Operating medium	Compressed air in accordance with ISO 8573-1:2010 [7:4:4]	
Note on operating/pilot medium	Operation with lubricated medium possible (in which case lubricated operation will always be required)	
Operating pressure [bar]	2 ... 10	
Ambient temperature [°C]	-5 ... +40	
Temperature of medium [°C]	-5 ... +40	
ATEX category for gas	II 2G	
Explosion ignition protection type for gas	c T6	
ATEX category for dust	II 2D	
Explosion ignition protection type for dust [°C]	40	
Explosion-proof temperature rating	-5 °C ≤ Ta ≤ +40 °C	
Explosion protection certification outside the EU	-	EPL Db (RU)
	-	EPL Dc (RU)
	-	EPL Gb (RU)
	-	EPL Gc (RU)
CE marking	To EU Explosion Protection Directive (ATEX)	
Corrosion resistance class CRC	1 ¹⁾	

1) Corrosion resistance class 1 according to Festo standard 940 070. Components subject to low corrosion stress. Transport and storage protection. Parts that do not have primarily decorative surface requirements, e.g. in internal areas that are not visible or behind covers.


Electrical data		
	Solenoid valve with F coil of choice	Solenoid valve with mounted solenoid coil
Electrical connection	Plug, 3-pin or cable, 3-wire	Cable, 3-wire
Operating voltage range	[V DC] 12, 24, 42, 48	24 ±10%
	[V AC] 24, 42, 48, 110, 230, 240 at 50 ... 60 Hz	-
Coil characteristics, 24 V DC [W]	-	0.8
Max. input power [W]	-	1.46
Max. input voltage [V]	-	48
Max. input current [A]	-	0.487
Effective inductance	-	Negligibly low
Effective capacitance	-	Negligibly low
Protection class to EN 60529	IP65 with plug socket	IP65 with plug socket
Switching time on [ms]	50	50
Switching time off [ms]	100	100

Solenoid valves NVF3, to NAMUR

Technical data




Materials




1	Housing	Anodised die-cast aluminium
2	Seals	NBR
		Contains PWIS (paint-wetting impairment substances)

Sample circuit

5/2-way valve



3/2-way valve with the option of exhaust air return




Solenoid valves NVF3, to NAMUR

Technical data

FESTO

Dimensions

Download CAD data → www.festo.com



Type	B1	B2	B3 ±0.1	B4 ±0.1	B5 ±0.1	B6	D1	D2 Ø	D3	H1	H2	H3 ±0.15	H4 ±0.15	H5 ±0.1	H6 ±0.1
NVF3-...	37	31	19	3	6.5	22	G¼	5.5	M5	102.4	88	47	24	12	46

Type	H7 ±0.15	H8 ±0.15	H9	H10	L1 ±0.2	L2 ±0.15	L3 ±0.1	L4	L5	L6	L7	L8	L9	L10
NVF3-...	25	23	136.4	153	53	32	27.7	76.5	49	12.5	84.7	57.2	85.3	57.8

Ordering data – Valves

Solenoid valve without solenoid coil¹⁾

Solenoid valve mounted with intrinsically safe solenoid coil

Part No. Type

Part No. Type

535987 NVF3-MOH-5/2-K-¼-EX






535988 NVF3-MOH-5/2-K-¼-IA-EX

1) Solenoid coil must be ordered separately → 10,
 Explosion-proof solenoid coil → 11


Solenoid valves NVF3, to NAMUR

Accessories

FESTO

Ordering data				
	Operating voltage	Cable length	Part No.	Type
F solenoid coil without plug socket Technical data → Internet: msfg, msfw				
	12 V DC	–	34410	MSFG-12-OD
	24 V DC	–	34411	MSFG-24/42-50/60-OD
	42 V DC	–	34413	MSFG-42-OD
	24 V AC/50 ... 60 Hz	–	34415	MSFW-24-50/60-OD
	42 V AC/50 ... 60 Hz	–	34411	MSFG-24/42-50/60-OD
	48 V AC/50 ... 60 Hz	–	34418	MSFW-48-50/60-OD
	110 V AC/50 ... 60 Hz	–	34420	MSFW-110-50/60-OD
	230 V AC/50 ... 60 Hz	–	34422	MSFW-230-50/60-OD
	240 V AC/50 ... 60 Hz	–	34424	MSFW-240-50/60-OD
Plug socket with screw terminal connection Technical data → Internet: mssd				
	–	–	34431	MSSD-F
	–	–	539710	MSSD-F-M16
Plug socket with insulation displacement connection Technical data → Internet: mssd				
	–	–	192746	MSSD-F-S-M16
Plug socket with cable Technical data → Internet: kmf-1				
	24 V DC	2.5 m	30935	KMF-1-24DC-2,5-LED
	0 ... 240 V DC/AC		30936	KMF-1-230AC-2,5
	24 V DC	5 m	30937	KMF-1-24DC-5-LED
	0 ... 240 V DC/AC		30938	KMF-1-230AC-5
Illuminating seal Technical data → Internet: mf-ld				
	12 ... 24 V DC/AC	–	19143	MF-LD-12-24DC
	230 V DC/AC	–	19144	MF-LD-230AC
Inscription label Technical data → Internet: kmc/f/v				
	–	–	33362	KMC/F/V-BZ-35X ¹⁾

1) Scope of delivery 35 pieces

 **Note**

Valve/solenoid coil combinations made up of a basic valve NVF3-MOH-5/2-K-1/4-EX and a solenoid coil MSF...-OD must not be used in hazardous areas.




Only combinations with the approved solenoid coil MSF...-EX may be used here.

→ 11

Solenoid valves NVF3, to NAMUR

FESTO

Accessories for ATEX environment

Ordering data				
	Operating voltage	Cable length	Part No.	Type
F solenoid coil for ignition protection type nA = non-sparking			Technical data ➔ Internet: msfw, msfg	
	24 V DC	–	536931	MSFG-24-EX
	24 V AC/50 ... 60 Hz	–	536932	MSFW-24-50/60-EX
	110 V AC/50 ... 60 Hz	–	536933	MSFW-110-50/60-EX
	230 V AC/50 ... 60 Hz	–	536934	MSFW-230-50/60-EX
F solenoid coil for ignition protection type mb			Technical data ➔ Internet: vacf	
	24 V DC	1 m	8059804	VACF-B-K1-1-1-EX4-M
	24 V DC	5 m	8059805	VACF-B-K1-1-5-EX4-M
	24 V AC/50 ... 60 Hz	1 m	8059808	VACF-B-K1-1A-1-EX4-M
	110 V AC/50 ... 60 Hz	1 m	8059811	VACF-B-K1-16B-1-EX4-M
	110 V AC/50 ... 60 Hz	5 m	8059812	VACF-B-K1-16B-5-EX4-M
	230 V AC/50 ... 60 Hz	1 m	8059809	VACF-B-K1-3A-1-EX4-M
	230 V AC/50 ... 60 Hz	5 m	8059810	VACF-B-K1-3A-5-EX4-M
	24 V DC	x m	8059807	VACF-B-K1-1-20-EX4-M
Plug socket with screw terminal connection for solenoid valve			Technical data ➔ Internet: mssd	
NVF3-MOH-5/2-K-¼-IA-EX, ignition protection type ia = intrinsically safe				
	–	–	539713	MSSD-V-M16