

## FG-100 5 µm (micron) 105 l/min · F1" BSP

**Liquids:**  **Diesel**  **Petrol**  **Biodiesel**

**Especially suitable for diesel**

FG-100 · 5 µm (micron) · water repellent filtering paper

39023

**Especially suitable for the transfer of gasoline, kerosene, AVGAS, JET A-1, diesel (ask for other liquids)**

FG-100G · 5 µm (micron)

39071

**Especially suitable for biodiesel**

FG-100BIO · 25 µm (micron)

39024

- *Diesel & Petrol* Filtration: **5 µm (micron)**
- *Biodiesel* Filtration: **25 µm (micron)**
- **Water decanter:** by **water repellent filtering paper**, with water decanting of 93 % (FG-100 & FG-100G)
- Capacity: **2 litres**
- Transfer capacity: **105 l/min**
- Upper microfilter housing: **aluminium**
- Housing: transparent
- Inlet / Outlet: **F1" BSP** flanges or threads
- Installation: **On the pumping kit suction or delivery**
- Max. working pressure: **5 bar**
- Vessel breaking pressure: **8 bar**
- Max. working depression: **-0,5 bar**
- Temperature: **-10 °C · + 50 °C**
- Drain valve

### IT IS SUPPLIED WITH

Housing (vessel) + filtering cartridge + **Key** for a QUICK replacing of the filtering cartridge, unscrewing its ring.

### Size and weight (approx.):

- Box Dim.: 190x230x330 mm (length x width x height)
- Box gross weight: 2.72 kg



### Optionals:

- Cartridge replacing key

660705000



- 5 µm (micron) paper filtering element spare kit + joints

660708001

- 5 µm (micron) paper filtering element spare kit + Viton joints 660708005

- 25 µm (micron) paper filtering element spare kit + joints 660708002



- F1" aluminium fixation flange

800003021



- FG-100 wall support

660704000