



Product Name	Technical Specifications
Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon " Size: 1/4-3/8	Flow Rate: 16 lit/min
	size inlet-outlet:1/4-3/8 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 1/4
	Solid handing capability:1.5 mm
	Weight: 1.2 Kg
	Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon Size: 3/4 "
Pump size inlet-outlet:3/4 inch	
Max discharge pressure:7 bar	
Max discharge head: 70 m	
Suction Depth: 6 m	
Liquid Temp Limit: -18 +100 C°	
Air inlet: 1/4	
Solid handing capability:3 mm	
Weight: 5 Kg	
Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon Size: 1 "	Flow Rate: 160 lit/min
	Pump size inlet-outlet:1 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4
	Solid handing capability:6 mm
Weight: 26 Kg	



Product Name	Technical Specifications
Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon Size: 1-1/2 "	Flow Rate: 400 lit/min
	Pump size inlet-outlet:1-1/2 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability:6 mm
	Weight: 40 Kg
Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon Size: 2 "	Flow Rate: 600 lit/min
	Pump size inlet-outlet: 2 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability:4 mm
	Weight: 60 Kg
Diaphragm pump Pump material: PP Diaphragm material: Santopern-Neoprene Teflon Size: 3 "	Flow Rate: 850 lit/min
	Pump size inlet-outlet:3 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability: 6 mm
	Weight: 85 Kg



Product Name	Technical Specifications
Diaphragm pump Pump material: Aluminium Diaphragm material: Santopern-Neoprene Teflon Size: 3/4 "	Flow Rate: 57 lit/min
	Pump size inlet-outlet: 3/4 inch
	Max discharge pressure: 7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 1/4"
	Solid handing capability: 3 mm
	Weight: 5.8 Kg
Diaphragm pump Pump material: Aluminium Diaphragm material: Santopern-Neoprene Teflon Size: 1 "	Flow Rate: 160 lit/min
	Pump size inlet-outlet: 1 inch
	Max discharge pressure: 7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 1/2"
	Solid handing capability: 4 mm
	Weight: 11 Kg
Diaphragm pump Pump material: Aluminium Diaphragm material: Santopern-Neoprene Teflon Size: 1-1/2 "	Flow Rate: 400 lit/min
	Pump size inlet-outlet: 1-1/2 inch
	Max discharge pressure: 7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability: 6 mm
	Weight: 26 Kg



Product Name	Technical Specifications
Diaphragm pump Pump material: Aluminium Diaphragm material: Santropern-Neoprene Teflon Size: 2 "	Flow Rate: 600 lit/min
	Pump size inlet-outlet: 2 inch
	Max discharge pressure: 7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4
	Solid handing capability: 6 mm
	Weight: 32 Kg
	Diaphragm pump Pump material: Aluminium Diaphragm material: Santropern-Neoprene Teflon Size: 3 "
Pump size inlet-outlet: 3 inch	
Max discharge pressure: 7 bar	
Max discharge head: 70 m	
Suction Depth: 6 m	
Liquid Temp Limit: -18 +100 C°	
Air inlet: 3/4	
Solid handing capability: 4 mm	
Weight: 51 Kg	



Product Name	Technical Specifications
Diaphragm pump Pump material: Stainless Steel(316) Diaphragm material: Santopern-Neoprene Teflon Size: 1 "	Flow Rate: 160 lit/min
	Pump size inlet-outlet:1 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 1/2"
	Solid handing capability:6 mm
	Weight: 12 Kg
Diaphragm pump Pump material: Stainless Steel(316) Diaphragm material: Santopern-Neoprene Teflon Size: 1-1/2 "	Flow Rate: 400 lit/min
	Pump size inlet-outlet:1-1/2 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability:6 mm
Weight: 26 Kg	
Diaphragm pump Pump material: Stainless Steel(316) Diaphragm material: Santopern-Neoprene Teflon Size: 2 "	Flow Rate: 565 lit/min
	Pump size inlet-outlet:2 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability:6 mm
Weight: 31 Kg	



Product Name	Technical Specifications
Diaphragm pump Pump material: Stainless Steel(316) Diaphragm material: Santopern-Neoprene Teflon Size: 3 "	Flow Rate: 894 lit/min
	Pump size inlet-outlet:3 inch
	Max discharge pressure:7 bar
	Max discharge head: 70 m
	Suction Depth: 6 m
	Liquid Temp Limit: -18 +100 C°
	Air inlet: 3/4"
	Solid handing capability:6 mm
	Weight: 65 Kg